

Standard Buff

A-1

**INVISIBLE
STONE
PATCHER**

Prepared for Indiana Limestone

USES:

For repairing minor damage to broken edges or corners of stone. Maximum patch size is ± 2 ".

INSTRUCTIONS FOR USE:

1. Surface to be patched must be completely clean and free from foreign materials. (Patcher will not bond properly to stone treated with sealers, etc.)
2. Wet area to be patched. (Stone which is too dry will absorb moisture from patcher and prevent proper cure.)
3. Mix patcher by adding clear water a little at a time until reaching a mortar-like consistency. (Do not add any more water once patcher has begun to set up.)
4. Apply patcher slightly heavier than the area to be patched.
5. Let dry for a minimum of 24 hours.
6. Area may be sanded after patcher has cured.

NOTE:

- Do not apply patcher when temperature is below 50° f. Patcher must not be subjected to freezing temperatures until it is completely cured.
- Do not mix any more patcher than you will use in a short time - as it sets quickly.
- Product shelf life is approximately 1 year if stored in a cool, dry place, and in tightly closed original containers.

IMPORTANT NOTICE:

The following is made in lieu of all warranties, expressed or implied. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, the user shall determine the suitability of the product for the intended use, and user assumes all risks and liability whatsoever in connection therewith. The foregoing may not be altered except by an agreement signed by officers of seller and manufacturer.

Average Weight: 7 lbs.

Galloy & Van Etten, Inc.

11756 S. Halsted Street

Chicago, Illinois 60628

773-928-4800

Fax 773-928-4129